

# RELIABILITY TEST PROCEDURES FOR ECS-3225MV Series



| <u>NO.</u> | <u>TEST NAME</u>                                               | <u>TEST PROCEDURES</u>                                                                                                                                                    | <u>REQUIREMENTS</u>                                       |
|------------|----------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| 1          | <b>SHOCK</b>                                                   | Drop 3 times from the height of 100cm onto hard wooden board.                                                                                                             | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 2          | <b>VIBRATION</b>                                               | Vibration Frequency: 10 to 55Hz, 1.5mm, full wave<br>Cycle: 2 min.<br>Direction: X.Y.Z.<br>Time: 2 hours in each direction                                                | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 3          | <b>STORAGE IN HIGH TEMPERATURE</b>                             | +85 ±2°C for 500 hours.                                                                                                                                                   | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 4          | <b>STORAGE IN LOW TEMPERATURE</b>                              | -40 ±2°C for 500 hours.                                                                                                                                                   | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 5          | <b>RESISTANCE TO SOLDERING HEAT</b>                            | Pass through reflow for 10s (Max.) which is pre-heated at a temperature of 160°C ± 10°C and 240°C ± 5°C                                                                   | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 6          | <b>HUMIDITY</b>                                                | + 60 ± 2°C in humidity<br>95% for 500 hours.                                                                                                                              | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 7          | <b>THERMAL SHOCK</b>                                           | Supply 500 cycles as follows:<br>Temperature shift shall be done within 30 sec.<br>-55 ±2°C                                    +125 ±2°C<br>(30 min)   <----->   (30 min) | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 8          | <b>TEMPERATURE CYCLE</b>                                       | Supply 100 cycles as follows:<br>                                                                                                                                         | Frequency Drift ±5 PPM Max.<br>Resistance Drift ±15% Max. |
| 9          | <b>SEALING TIGHTNESS MIL-STD 202F METHOD 112D TEST C AND D</b> | 1) Dipping in Florinert at:<br>+125 ±5°C for 5 min.<br>(Gross Leak)                                                                                                       | There are no visual abnormalities.                        |
|            |                                                                | 2) Leak rate shall be measured by using:<br>Helium leak Detector<br>(Fine Leak)                                                                                           | There are no visual abnormalities.                        |
| 10         | <b>Mean Time Between Failures (MTBF)</b>                       | $MTBF (25^{\circ}C) = \frac{E_a \times (1/T_1 - 1/T_2) / K}{\pi}$                                                                                                         | 16396600 Hours                                            |