

RELIABILITY TEST PROCEDURES FOR ECX-53 Series



| <u>NO.</u> | <u>TEST NAME</u> | <u>TEST PROCEDURES</u> | <u>REQUIREMENTS</u> |
|-------------------|--|--|---|
| 1 | SHOCK | Drop 3 times from the height of 100cm onto hard wooden board. | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 2 | VIBRATION | Vibration Frequency: 10 to 55Hz, 1.5mm, full wave Cycle: 2 min. Direction: X.Y.Z. Time: 2 hours in each direction | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 3 | STORAGE IN HIGH TEMPERATURE | +85 ±2°C for 500 hours. | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 4 | STORAGE IN LOW TEMPERATURE | -40 ±2°C for 500 hours. | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 5 | RESISTANCE TO SOLDERING HEAT | Pass through reflow for 10s (Max.) which is pre-heated at a temperature of 160°C ± 10°C and 240°C ± 5°C | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 6 | HUMIDITY | + 60 ± 2°C in humidity 95% for 500 hours. | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 7 | THERMAL SHOCK | Supply 500 cycles as follows: Temperature shift shall be done within 30 sec. -55 ±2°C +125 ±2°C (30 min) <-----> (30 min) | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 8 | TEMPERATURE CYCLE | Supply 100 cycles as follows: +25 ±5°C 10 min. -55 ±3.5°C 30 min. +125 ±5 -2°C 30 min. 1 Cycle | Frequency Drift ±5 PPM Max. Resistance Drift ±15% Max. |
| 9 | SEALING TIGHTNESS MIL-STD 202F METHOD 112D TEST C AND D | 1) Dipping in Florinert at: +125 ±5°C for 5 min. (Gross Leak) | There are no visual abnormalities. |
| | | 2) Leak rate shall be measured by using: Helium leak Detector (Fine Leak) | There are no visual abnormalities. |
| 10 | Mean Time Between Failures (MTBF) | $MTBF(25^{\circ}C) = \frac{HsXe^{\frac{Ea}{Ce}}}{\pi}$ | 16396600 Hours |